

PLSS Corner Collection System Data Sheet

Meridian: PMM Tier: 16N Range: 53E Section(s): 8, 9, 16, 17 County: Dawson

GCDB Point ID: **M T 2 0 0 1 6 0 N 0 5 3 0 E 0 3 0 0 5 0 0 A C C**

Employee Name: JD Ingraham

Date: 6/16/2011

Time: 4:15

Found: Tied 4"x4" wood stake, 18" above ground. Original notes – 1883 – page 40 (image 1883-MTRO1020400)
"deposit marked stone 12ins. In ground, dig pits 5 1/5' distant, NW, NE, SE, SW of corner." Set wood stake in SE pit.
Original notes are very hard to read. The selection of the SE pit is based on the instructions in the 1902 BLM
manual. The collected wood stake is 5' East of a 6" wood fence corner post with fences running North, South, and
West. Post is 42' North 6" wood post with Fences running North, South, and East. No visible marks on post.
NOTE: Actual corner location calculated from this accessory using record bearing and distance of 5.5' Northwest
of the collected position.



Latitude: 47°09'09.8611" N

Longitude: 105°01'36.7191" W

Datum:

NAD83(2007)Approximate orthometric elevation: 2628 ft.

This corner was located as part of a PLSS enhancement project. The location of this corner was not used as control for any legal surveys during this exercise. Horizontal accuracy 1 meter or less.